

SVE wood finish Melamine Top Coat

SVE Wood Finish Melamine Topcoat is an acid curing solvent 2 pack quality product, which is formulated specially for the protection of your wood, and helps preserving the shininess of the wood for longer years.

It is specially formulated as a protective & decorative clear finish for woods oil, food and beverage stains thus maintaining natural beauty of wood for year

- Method of Application: Spray
- Dilution: SVE Thinner (T-14)
- Drying Time: Surface dry – 30 to 60 minutes
- Recoat time: At an interval of 6 to 12 hours
- Shade : Transparent.
- It provides a, durable film which helps protecting your wood from water, alcohol and usual household chemicals, thus giving attractive finish to the surface of protection.

Technical Details:

- Coverage: 8 -10 sq meter/Ltr/Coat
- *Note: Actual coverage may vary from quoted coverage due to factors such as method, condition of application & surface roughness*
- Drying Time : Surface dry time: 10 minutes, Tack Free time -1 hr

Directions for use:

Mixing ratio of Melamine Sanding Sealer & Melamine Hardner – 9:1 by volume

Keep the mixture for 20 -30 minutes for maturation.

Mix the above mixture with 20 -40 % of SVE T-14 Thinner and use it within 8 hrs.

Keep the mixture for 20- 30 minutes for maturation. Spray by using SVE T14 Thinner.

Consume the mixture in 4 -6 hrs. Allow it to dry for 6-8 hrs

It is available in glossy, Satin and mat finish in the following variety

- SVE Wood Finish Melamine Premium Glossy
- SVE Wood Finish Melamine Clear Glossy (WW)
- SVE Wood Finish Melamine Matt
- SVE Wood Finish Melamine Semi-Matt
- SVE Wood Finish Melamine Premium Matt (WW)
- SVE Wood Finish Melamine Satin

Pack: 1litre, 4 litre, 20 litre