

SVE Wood Finish PU Sanding Sealer

SVE Wood Finish PU Sanding Sealer is used for preparing surface of wood before applying PU base top coat. It provides uniformity and smoothness to the surface for top coating

PU sealer acts as a protection cover, saving it from various blemished marks and streaks

Technical Details:

- Method of Application –Spray
- Recommended Thinner –SVE T 10
- Drying Time : Surface Dry time – 10 minutes ,Tack free time – 1 hr
- Coverage: Coverage: 8 -10 sq metre/Ltr/Coat

Note: Actual coverage may vary from quoted coverage due to factors such as method, condition of application & surface roughness

Directions of Use:

Mixing Ratio: PU Sanding Sealer & PU Hardner: 8:2 Parts

Mix the above mixture with 30- 40% T10 Thinner

- Apply 2 coats of SVE PU wood sanding sealer with a gap of 45 minutes and then sand it after overnight in order to remove the unwanted particles on the wooden surface, sand the surface with emery paper no. 320/400.Examine the surface for imperfection, if any touches with sealer make it smoother as per process mentioned above.

Pack Available: 1litre, 4litre, 20litre

Variety of PU Sanding Sealer:

SVE Wood Finish PU Sanding Sealer

SVE Wood Finish PU Sanding Sealer White

SVE Wood Finish PU Sanding Sealer Brown